HP Latex R1000 Plus Printer



Help grow your business by printing high-value jobs on one device with white 1, rigid and flexible





Get amazing colours, rigid and flexible up to 1.6 m (64 in)

- Grow your business into higher value rigid/flexible jobs with vibrant HP Latex gamut, media look and feel.
- Gain versatility with HP Latex Ink from indoor/outdoor signage to thermoforming and high-quality decoration.
- Win more jobs with UL ECOLOGO® Certified, water-based HP Latex Inks that produce odorless prints.²

We've removed the barriers to print with white 1

- Expand your portfolio into a wide range of applications with glossiest white that resists yellowing ¹
- No waste between white jobs³ with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- You're always ready to print white automatic recirculation and printhead cleaning eliminate manual purging.

Manage your peaks in-house with smart printing

- Meet production peaks get high-speed quality up to 15 outdoor boards/hr⁴ with belt system, smart vacuum
- Help avoid costly operating errors with an easy interface including advanced queuing and multiboard printing.
- Maximise uptime with automatic maintenance and smart service tools for fast diagnosis and issue resolution.
- Maintain control of your production and costs with the help of HP PrintOS software tools.

For more information, please visit http://www.hp.com/go/LatexRseries

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

considerations (see http://www.ul.com/EL). There is a broad set of media with very different odor profiles. Some of the adia can affect the odor performance of the final print hence when the final print the second in the storage cassettes, no white ink is used for servicing when printheads are not in use.

¹ Glossiest white based on internal HP testing in January, 2018 compared to the HP Scitex FB750/FB550 Printer using UV-curable ink technology. White ink measured for the level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure. High opacity and resists yellowing over time based on internal HP WeatherOmeter testing October, 2017 with 1 dot-per-pixel HP Latex Overcoat, on a range of rigid and flexible unlaminated substrates. Yellowing based on L* and B* of white underflood samples.

2 HP Latex Inks are UL ECOLOGO® Certified. UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to unuman health and environmental

⁴ Outdoor mode 3-pass, 70%. On 1.2 x 2.4 m (4 x 8 ft) boards

Technical specifications

Print

15 m²/hr - Indoor High Quality (12p 120%) 28 m²/hr - Indoor Production (6p 110%) 55 m²/hr - Outdoor (3p 70%) 25 m²/hr - Outdoor (3p 70%) 25 m²/hr - White Spot (100%) 11 m²/hr - White Overflood (100%) 3.6 m²/hr - 3 layers day & night¹ Up to 1200 x 1200 dpi Water-based HP Latex Inks 9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimiser, HP Latex Overcoat, white) 3 L 8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimiser, 2 white) Average ≤ 1.0 dE2000, 95% of colours ≤ 2 dE2000² Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
Water-based HP Latex Inks 9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimiser, HP Latex Overcoat, white) 3 L 8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimiser, 2 white) Average ≤ 1.0 dE2000, 95% of colours ≤ 2 dE2000² Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimiser, HP Latex Overcoat, white) 3 L 8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimiser, 2 white) Average \$ 1.0 dE2000, 95% of colours \$ 2 dE2000^2 Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive viryl, coated paper, polypropylene, polystyrene, polycarbonate, polyeste, textile (non porous), canvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
3 L 8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimiser, 2 white) Average ≤ 1.0 dE2000, 95% of colours ≤ 2 dE2000² Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polycarbonate, polyester, textile (non porous), canvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimiser, 2 white) Average ≤ 1.0 dE2000, 95% of colours ≤ 2 dE2000 ² Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
Average ≤ 1.0 dE2000, 95% of colours ≤ 2 dE2000 ² Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), carvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), carvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), carvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC banner, self-adhesive vinyl, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), carvas, leather 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of optional extension tables) 60.9 cm to 1.63 m
60.9 cm to 1.63 m
Up to 68 kg
Up to 25 cm
Up to 50.8 mm
Signage: indoor, flat, backlit, thermoformed; Decoration: wall coverings, window decoration; Vehicle decoration: fleet graphics, wraps, decals; Textile: soft signage, frontlit, backlit; POS and Packaging: corrugated displays, short-run customized packaging, prototyping
Gigabit Ethernet (1000Base-T)
)
4.21 x 2.04 x 1.75 m (printer); 4.21 x 3.64 x 1.75 m (including standard input and output tables)
4.43 x 2.24 x 2.15 m
6.61 x 6.03 x 3 m
1400 kg
2400 kg
HP Latex R1000 Plus Printer; HP Latex R Series White Upgrade Accessory Kit; HP Latex R1000 Roll Printing Accessory Kit with 64 in spindles (x2) and pneumatic gun adapter and table top roll holders (x2); HP 886 Latex Printheads; HP Latex Printhead cleaning kit; Standard input and output tables; Foot switch; HP Internal Print Server and displays (x2); Printer maintenance kit; Warranty and intro docs.
;
15 to 30°C
20 to 70% RH (non-condensing)
8 to 10 kW (typical)
IEC 60950-1+A1+A2 compliant; EU (LVD and MD compliant, EN60950-1, EN12100-1, EN IS013849-1, EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC)
Compliant with Class A requirements, including: EU (EMC Directive)
WEEE; RoHS (EU, Turkey, Ukraine); REACH; ErP Ecodesign Directive
1 year Maintenance and Support coverage: Six-month limited hardware warranty; 6 months HP Standard Service, Maintenance and Support. Warranty may vary by country as required by law. Go to http://www.hp.com/support to learn about HP service and support options in your region.
1 2 FAFS 1 2

Ordering information

Product

K0Q45A	HP Latex R1000 Plus Printer
Accessories	
T7V21A Y6V16A	HP Latex R1000 Extension Tables HP Latex R Series Edge Holders Kit

Original HP printing supplies

GOZO0A HP 886 GOZO1A HP 872 GOZO2A HP 872 GOZO3A HP 872 GOZO4A HP 872 GOZO5A HP 872 GOZO6A HP 872 GOZO7A HP 872 GOZO7A HP 872	Latex Printhead Latex Printhead Cleaning Kit 3-liter Cyan Latex Ink Cartridge 3-liter Magenta Latex Ink Cartridge 3-liter Pilow Latex Ink Cartridge 3-liter Pilow Latex Ink Cartridge 3-liter Black Latex Ink Cartridge 3-liter Light Cyan Latex Ink Cartridge 3-liter Light Magenta Latex Ink Cartridge 3-liter Optimizer Latex Ink Cartridge 3-liter Optimizer Latex Ink Cartridge 3-liter Optical Latex Ink Cartridge 3-liter White Latex Ink Cartridge
GUZU9A HP 886	3-liter White Latex ink Cartriage

Original HP large format printing materials

HP Premium Removable Gloss Adhesive Vinyl HP Permanent Gloss Adhesive Vinyl HP Durable Backlit Fabric (Take-back program)³ HP Backlit Polyester Film (Take-back program)³

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

If you want to extend the support beyond what's included: If you want to extend the support beyond whats included: HOHXA4C HP Standard Service, Maintenance and Support extension contract HOIR1AC HP Enhanced Service, Maintenance and Support extension contract UASWOS HP Latex R series Level 3 Train to repair and maintain – 5 days training at HP UA3Q7E 3 Years Next Business Day with Defective Media Retention for HP Latex R1000 Plus K0Q45-67269 HP Latex R series Expert spare parts uptime kit

ECO highlights

- Better for the environment – HP designs end-to-end sustainability into large-format
- printing

 Water-based inks produce odorless prints²

 HP Latex Inks are UL ECOLOGO® and UL GREENGUARD GOLD Certified³

Please recycle large-format printing hardware and printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

¹ Contains no Hazardous Air Pollutants according to EPA Method 311. Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer – see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.

² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

³ UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see http://www.ul.com/EL). UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to ULS GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to ULS GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.ul.com/gg.or

¹ Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.
² Reflective measurements on a 943 colour target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Back-lit substrates measured in transmission mode may yield different results.
³ Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.









